HUAWEI EG8245Q

Installation

INTRED
CONNESSI SEMPRE





F
Fibre

BUTTON FUNCTIONS

LEFT SIDE:

- *WLAN:* switches the wireless network on and off.
- *WPS:* creates the connection with WPS.
- *LIGHT:* switches the LEDs on and off.
- *RESET:* resets to factory settings. Do not press.

LED MEANINGS

LED	STATUS	MEANING
POWER	ON	Power available
PON	ON	Line present
LOS	FLASHING	No line
TEL 1-2	ON	VoIP line present
LAN 1-4	FLASHING	Data transfer with a cable-connected device
WLAN	ON	The wireless network is active
WPS	FLASHING	• WPS pairing in progress • Can be enabled via the web interface (disabled by default)
USB	ON	USB port for sharing local files

ENJOY BROWSING!


HUAWEI EG8245Q

Installation

INTRED
CONNESSI SEMPRE


WARNINGS


- To use the router, use the power supply provided or a device compatible with the electrical specifications of the unit.
- NEVER restore the router to factory settings with a reset. Doing so could mean the router has to be replaced.
- The password for the WiFi network is on the label on the back of the device, next to WLAN Key.
- The router's username and password are next to the corresponding entries Username and Password.



PORTS

- *Fibre(green):* port for the fibre connection via the green connector. The port is located underneath the router.
- *Tel 1:* RJ11 socket for connecting an analogue phone or another analogue terminal device (if included in the contract).
- *Tel 2:* not usable.
- *LAN 1-4:* four Ethernet ports for connecting computers and other network devices.
- *USB:* USB port for sharing local files.






CONNECTING THE CABLES

- *POWER PORT:* connection to the mains

1. Take the power supply provided with the HUAWEI router.
2. Connect the power supply to the HUAWEI power socket.
3. Plug the power supply into the mains socket.
4. Press the On/Off button: the POWER light will come on.



- *WALL OPTICAL PORT:* fibre optic connection

1. After removing the protective cap from the green connector, insert one end of the cable into the optical port installed by the technician during installation.
2. After removing the protective cap from the other end of the green connector, connect it to the green fibre port on the back of the router (as shown in the figure).

This document is an English translation of the original Italian document and is provided for ease of reference. The translation may contain errors, omissions or inaccuracies. In the event of any discrepancy or inconsistency between this translation and the Italian original, the Italian original shall prevail to the extent permitted by applicable law.